

# Petticrows— Rig set up guide. 2011

When setting up a Petticrows Dragon there are some basic steps to follow. This way you can be sure the boat is set up in a “standard” way. If you use these settings as a base reference you can then experiment to find out exactly what suits your sailing



## 1. Set the jumper tension

If you have fixed jumpers then set the tension prior to stepping the mast.

An average setting would be 8 on a Loos Tension gauge. Check the mast is straight sideways.

On adjustable jumper systems mark the overall tension control rope with 6,8 and 10. ( this can only be measured when the mast is up and from a ladder)



## 2. Mark the forestay

Put the mast up in the boat, so that it is standing vertically.

Measure from the deck -up the mast 81cm and make a mark. (max class rule is 81mm, min79mm)

This will probably be at the top of your black band.

Pull the forestay down the mast and mark the forestay at the mark which is 81cm up the mast.

The mark on the forestay is your reference



## 3. Establish the mast rake.

Connect the forestay.

Do not connect the mast ram bottle screw or shrouds.

Get some tension on the forestay with a little runner or backstay tension.

Measure from the mark on the forestay to the deck.

This measurement is your mast rake.

Pin in medium setting hole. Light and strong wind positions either side



The average mast rake measurement should be 122cm.

In heavy winds the mast can be raked aft so that the mast rake measurement is 123cm.

In light winds. The mast can be raked forwards so that the mast rake measurement is 121cm

If the rake is incorrect it can be altered by changing attachment point of the forestay.

It is a good idea to tape above and below the most commonly use holes.

#### **4. Find station 4 line**

On the topsides of the boat just below the edge of the deck there are small spots which show the position of measurement stations. Station 4 is about 1200mm in front of the mast

With a straight edge and some tape join the station 4 marks across the deck of the boat.

This line across the deck will be your reference for your mast, forestay and shroud position.



#### **5. Find shroud positions**

Measure from station 4 line perpendicularly to the front face of the upper shroud.

This measurement should be 82 cm

Measure from the station 4 line to the front face of the lower shroud.

This measurement should be 85cm

It is normal to have the shrouds inline with the front of the mast when sailing upwind. Moving them aft from this position has the effect of making the mast bend less.

Forward of inline and the mast will bend more.



#### **6. Find forestay measurement plate position**

Measure from station 4 line to the front of the *forestay plate*.

This measurement should be 104cm

The plate can be 75mm long

The forestay must be within the front and back of this plate.

We always put the forestay at the front of this plate.



#### **7. Find mast measurement plate position**

Measure from station 4 line to the aft of the *mast measurement plate*.

This measurement should be 82cm.

This plate is 50mm long.

#### **8. Check the “J” measurement**

The J measurement is the distance between the front of the *forestay measurement plate* and aft of the *mast measurement plate*.

This should be a maximum of 186 cm as per class rules

## **9. Mast step position and pre bend**

Without connecting the mast ram bottle screw  
OR shrouds

And with the mast rake at 122cm

Push the mast aft so that the forestay has some tension. You can use a little runner tension to achieve this. Do not bend the mast.

Normal position of the mast is that the front face is level or aft of the aft end of the *mast measurement plate*.

If the front of the mast is level there will be no pre bend when you connect and adjust the mast ram bottlescrew. If you are ( as an example ) 5mm behind , you will have 5mm of prebend when you connect and adjust the bottlescrew .

It is normal to have between 0 and 10mm of pre-bend.

If the mast is more than 10 mm behind the aft end of the *mast measurement plate* , this indicates the mast step pin needs to be moved FORWARD.

If the mast is in front of the *mast measurement plate* , this indicates the mast step pin must be moved AFT.



## **10. Connect Shrouds and adjust Mast Ram Bottle-screw.**

Connect the shrouds in the chosen shroud position and wind the upper shroud nut to achieve a tension of 15 on the Loose gauge. Make sure the shroud calibration marks are equal port and starboard.

Connect the lowers in the next hole aft and wind the shroud nuts to achieve a tension of 10. Again make sure the calibration marks are equal.

Connect the Mast Ram Bottlescrew to the mast. Pull tension on the runners.

Adjust the bottlescrew open or closed so when the lever is pulled **maximum aft** the front of the mast is level with the aft of the *Mast Measurement plate*. Using the locking nuts fix bottle screw in this position..

Sight up the mast and if the mast step position is correct the mast will be straight fore/aft or have a forward bend of up to 10mm . (The Pre-bend.).

To check the forward movement of the mast ram. Release the runners and backstay. Uncleat the mast rope controlling the lever so the bottlescrew pushes the mast forward. In this position the front of the mast must not be further forward than the front of the *Mast Measurement Plate*.

If it does then you must restrict it from exceeding the class rule maximum movement of 50mm.



### **11. Measure the shroud tension**

Using a Loos Model PT-2M tension meter set the shroud tensions depending on the weather conditions.

Measure directly onto the wire.

The figures given are for boats newer than 2008, in older models of boat the hull is not so stiff so up to 30% more tension is required



### **12. Mark your Maximum Runner Tension.**

Attach a Loos Gauge to the fore-stay.

Pull on the runner until the tension is 32.

Put a mark on the runner wire where it enters the deck. This can be used as a guide to runner tension while sailing

32 is the absolute maximum in strong winds..

## Petticrows rig settings guide—Summary

Jumper average tension	8
Average mast rake measurement	122 cm
Mast rake light wind	121 cm
Mast rake strong wind	123 cm
Station 4 line to front upper shroud	82 cm
Station 4 line to front lower shroud	85 cm
Station 4 measurement to front of forestay measurement plate	104 cm
Station 4 line to aft of mast measurement plate	82 cm
Maximum runner tension (measured on forestay)	32

**Please note :**

**The shroud positions and forestay positions detailed are the current measurements put on 2011 boats for best balance.**

**On Older Petticrows boats the *mast measurement plate* and *forestay measurement plate* would have been fitted in the optimum position for that age of boat.**

**Check these measurement plate positions and adjust the shroud and forestay positions using the same principles as detailed above.**

## Rig tension guide Standard mast

Light winds	Medium winds	Strong winds
Lower shroud 0	Lower shroud 5-10	Lower shroud 15
Upper shroud 12	Upper shroud 15	Upper shroud 20-25
Upwind Mast Ram Forward from max aft by 1-1.5 cm	Upwind Mast Ram  Max aft	Upwind Mast Ram Forward from max aft by 1-1.5 cm

## Rig tension guide New Stiff ‘I’ mast

Light winds	Medium winds	Strong winds
Lower shroud 0	Lower shroud 5-8	Lower shroud 10-12
Upper shroud 10	Upper shroud 14-15	Upper shroud 16-20
Upwind Mast Ram Forward from max aft by 1-1.5 cm	Upwind Mast Ram  Max aft	Upwind Mast Ram Forward from max aft by 1-1.5 cm

**Caution.**

The lower shroud tensions given are a guide only and for any chosen upper shroud tension the Lower shroud tension can only be correctly achieved by sailing upwind , sighting up the mast and adjusting the lower shroud tension until the mast is straight sideways.